



TEX DYE CHEM

www.texdyechem.com

TDC-25W (Rubber white paste)

TDC-25W is a homogeneous, white paste formulated for table printing applications. Its composition delivers an elastic, smooth finish with enhanced white coverage, making it a great choice for table printing.

Highlights

- Does not dry during the printing process or block the screen when used as recommended.
- Provides an elastic, soft, feel-less texture with excellent coverage.
- Offers good wash fastness.
- Rubbing and washing tests should be conducted at least 24 hours after curing.

Printing Tips

- All water based pastes can be colored with this product.
- It can be mixed with TDC-25C in any ratio.

Compliance

- Complies with international ecological and environmental standards

Precautions

- Stir well before use.
- Do not add any unapproved additives.
- Clean the screen with water and a sponge immediately after use.

Packaging

- Available in 25 kg buckets and 30 kg & 60 kg drums.

Storage & Shelf Life

- Store in a cool, dry place away from direct sunlight.
- Keep the container tightly closed after each use.
- Shelf life: 6 months in unopened, sealed containers.

Disclaimer

- The technical information provided above is intended as guidance for application only and should not be considered a warranty for other uses.
- Please refer to the Safety Data Sheet (SDS) for detailed hazard and safety information. The manufacturer/distributor shall not be held responsible for any direct or indirect loss or damage arising from improper or non-conforming use of the product.

Screen Mesh

Counts: 40T-54T

Squeegee

Durometer: 55-60 Shore

U type dr. blade

Cure Temperatures

320°F (160°C) for 1 minute

Additives

Do not use any additives that are not advised

Shipping & Storage

77°F - 95°F (25°C - 35°C)

Clean Up

Water and sponge

Health & Safety

Please see: Safety Data Sheet



13, Mehboob chamber, rampart row,
Jodia Bazar, Karachi, Pakistan



+92 3232982225



info@texdyechem.com